

WOS series

WATER - OIL SEPARATORS

|                       |              |
|-----------------------|--------------|
| operating temp. range | 1,5 to 45 °C |
|-----------------------|--------------|



| WOS SERIES |                                                     |            |     |      |       |                     |
|------------|-----------------------------------------------------|------------|-----|------|-------|---------------------|
| WOS MODEL  | Flow rate                                           | Dimensions |     |      | Mass  | Filter element type |
|            | 15 °C 60%RH / 25 °C 60%RH / 40 °C 100%RH<br>[Nm³/h] |            |     |      |       |                     |
| WOS 4      | 4,82 / 4,04 / 2,05                                  | 416        | 243 | 411  | 2.77  | PP,AK, WOS 4        |
| WOS 8      | 10,0 / 8,4 / 4,25                                   | 730        | 343 | 680  | 11.77 | PP,AK, WOS 8        |
| WOS 20     | 24,4 / 20,5 / 10,37                                 | 820        | 366 | 940  | 16.23 | PP,AK, WOS 20       |
| WOS 35     | 42,3 / 35,5 / 17,99                                 | 960        | 386 | 1137 | 21.54 | PP,AK, WOS 35       |

REMARK  
- Prices are for housings only (with water quality test kit).



FILTER ELEMENTS

| Filter element type | Corresponding housing | PP | AK |
|---------------------|-----------------------|----|----|
| WOS 4               | WOS-4                 |    |    |
| WOS 8               | WOS-8                 |    |    |
| WOS 20              | WOS-20                |    |    |
| WOS 35              | WOS-35                |    |    |



Remarks:  
- Both elements are required.

WATER QUALITY TEST KIT

